

APPLICATION and PERFORMANCE SPECIFICATION

ACT2P28RS120N

- Line Voltage: 120V 60Hz
- Program Start
- Lamp End of Life Protection
- Normal Power Factor Correction

Lamp Type	Lamp No.	Rated Lamp Watts	Min. Start Temp. (F/C)	Input Voltage (Vols)	Input Current (Amps)	Input Power (Watts)	THD ≤%	PF ≥	CF ≤	BF	BEF
* F28T5	2	28	0/-18	120	0.96	60	140	0.50	1.7	0.90	1.50
F21T5	2	21	0/-18	120	0.78	44	160	0.50	1.7	0.92	2.09
F14T5	2	14	0/-18	120	0.62	31	175	0.47	1.7	1.05	3.38

Note: the above data is tested at 60Hz. Application and Performance Specification Information Subject to Change without Notification.

Performance

- Meets Energy Star Version 1.0
- Meets FCC Part 18 (Class B) for EMI

Application

- Maximum Ambient Temperature: 131°F, 55°C
- Sound Rated: A
- Maximum case temperature Tc: 167°F, 75°C
- Remote Mounting: 18ft. max. Lead length, 18AWG

Lead length

White, Black	18" (±1")
Red, Blue	18" (±1")
Yellow	38" (±1")

Safety

- No PCB'S, Type HL
- UL & cUL listed (Class P, Type 1 Outdoor)
- OCV 300V

Physical Parameters

• Length	9.08"
• Width	0.9"
• Height	0.9"
• Mounting:	8.75"
• Weight	0.67lbs

