



APPLICATION and PERFORMANCE SPECIFICATION

ACT1P32IS120

- Line Voltage: 120V 60hz
- Instant Start
- Parallel Lamp Operation
- Passive Power Factor Correction

Lamp Type	Line Volt.	Num. Of Lamps	Rated Lamp Watts	Min.Start Temp. (F/C)	Input Current (Amps)	Input Power (Watts)	MAX. THD%	Power Factor	Ballast Factor	MAX.Lamp Current Crest Factor	B.E.F.
*F32T8	120	1	32	0/-18	0.26	30	20	0.98	0.88	1.7	2.90
F25T8	120	1	25	0/-18	0.22	25	30	0.96	0.89	1.7	3.55
F17T8	120	1	17	0/-18	0.17	18	30	0.91	0.94	1.7	5.25
F25T12	120	1	25	0/-18	0.22	26	30	0.96	0.91	1.7	3.50

Application and Performance Specification Information Subject to Change without Notification.

Performance:

- Meets ANSI Standard C82.11-2002
- Meets ANSI Standard C62.41-2002
- Meets FCC 18 CONSUMER limits

Application:

- Remote Mounting: 18 ft. max. Lead length, 18AWG
- Maximum Ambient Temperature: 131°F, 55°C
- Sound Rated: A
- Maximum case temperature (Tc) : 194°F, 90°C

Safety:

- No PCB's, Type HL
- UL& cUL listed (Class P, Type 1 Outdoor)
- OCV 600V

Physical Parameters:

- Length: 9.5" Width: 1.3" Height: 1.0"
- Weight: 1.1 lbs
- Lead Length: White, Black 25" (±1")
- Red 46" (±1")
- Blue 31" (±1")

