



APPLICATION and PERFORMANCE SPECIFICATION

ACT2S26PSUNV

- Line Voltage:120-277V 50/60Hz
- Series Lamp Operation
- Lamp End of Life Protection
- Program Start
- Active Power Factor Correction

Lamp Type			Min. Start	Vin	Iin	Pin	ATHD	PF	CF	Lamp
Type	No.	Watts	Temp. (F/C)	(V)	(A)	(W)	≤%	≥	<	current(A)
	1	20-50	0/-18	277	0.084-0.21	23-57	10	0.98	1.70	0.26-0.31
	2	26	0/-18	277	0.11	30	10	0.98	1.70	0.26-0.31

Note: the above data is tested at 60Hz. Application and Performance Specification Information Subject to Change without Notification.

UL&cUL is in application

Performance

Meets ANSI Standard C82.11-2002
 Meets ANSI Standard C62.41-2002
 Meets FCC 18 Non-CONSUMER Limits

Safety

No PCB's,
 UL listed (Class P, Type 1 Outdoor)
 OCV 300V
 No-load Power :< 5W

Application

Maximum Ambient Temperature: 131°F,55°C
 Remote Mounting: 18 ft. max. Lead length, 18AWG
 Sound Rated: A
 Maximum case temperature Tc: 194°F,90°C

Physical Parameters

Length 5.05" 128.3(mm)
 Width 2.42" 61.4(mm)
 Height 0.9" 23.0(mm)
 Mounting 4.66" 118.4(mm)
 Weight 0.48 lbs / 220g



APPLICATION and PERFORMANCE SPECIFICATION

